

SELENIA WR 5W-40 Cod. 1092

DESCRIPTION

Highly selected synthetic based oil for direct injection engines, both aspirated and turbo-charged. It is developed to respond to all requirements of the latest generation diesel engines (common-rail), where the revolutions per minute and the specific power of the engine are enhanced. As a result of the particular additives, it also ensures complete protection of the engine. Recommended by Fiat / Lancia / Alfa Romeo for Multijet engines.

CHARACTERISTICS

SELENIA WR is formulated with a correct balance of the detergent additives and dispersants that help to reduce and control the formation of deposits, combustion residue and carbon deposits guaranteeing the optimal operation of the engine.

- The advanced viscosity grade 5W-40 ensures the use of the product in more extreme temperatures:
SAE 5W allows excellent lubrication and engine start up to -30°C;
SAE 40 guarantees the lubrication film with external temperatures up to +40°C.
- Minor fuel consumption and reduced emissions
- Thermal stability preventing oxidation;
- Wear reduction;
- Special formula "air release" to grant idraulic tappets control;
- Particularly suited to JTD or common rail engines where the revolutions per minute and the specific power of the engines are enhanced.



ADVICE ON USE

Replacement should be as indicated by Fiat.

RECOMMENDED BY

Fiat, Lancia, Alfa Romeo for Multijet engines and cold climates.

TECHNICAL DATA

SAE 5W-40, ACEA B3/B4, API CF, FIAT 9.55535-N2 CONTRACTUAL TECHNICAL REFERENCE N°F515.D06, MB-Approval 229.3, VW 505.00, VW 502.00, GM-LL-B-025